

GH1.25 Series Terminal Wire

1.25mm pitch - JST GH series compatible

Parameter	Value
Pitch	1.25mm
Wire Gauge	28AWG - 32AWG
Rated Voltage	50V AC/DC
Rated Current	1A
Temperature Range	-25°C ~ +85°C
Insulation Material	PVC / UL1571
Contact Material	Phosphor Bronze, Tin Plated
Positions	2P to 15P
Custom Length	30mm - 1000mm

Applications

- LED lighting
- Small home appliances
- Consumer electronics
- Smart home devices

Available Configurations

- Both ends stripped and tinned
- One-end or both-end housing
- Color options: Red, Black, White, Yellow, Blue or custom
- Gold-plated terminal and high-temperature options available on request

Certifications & Compliance

- UL 1571 rated wire
- RoHS 2.0 compliant
- REACH SVHC compliant

Manufacturing & Lead Time

- 15 fully automatic crimping machines
- In-process pull-force testing, 100% continuity testing and 100% visual inspection before shipment
- MOQ: 3,000 pcs per specification (samples from 50 pcs; small batches negotiable)
- Sample lead time: 2-3 days | Mass production: 5-10 days | Small batch accepted
- Trade terms: FOB Shenzhen / Guangzhou (EXW negotiable)

DONGGUAN JIAYU ELECTRONICS CO., LTD.

Room 302-1, Building 1, No. 32 Tongfu East Road, Shijie Town, Dongguan, Guangdong, China

Tel: +86 134-8028-4505 (Lairy Lai) | Email: sales@jiayu-elec.com | Web: www.jiayu-elec.com

All specifications are subject to confirmation with our engineers for your exact application. Customization available.